

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 09-153882

(43)Date of publication of application : 10.06.1997

(51)Int.Cl.

H04J 11/00
H04J 1/20
H04L 27/34

(21)Application number : 08-043854

(71)Applicant : VICTOR CO OF JAPAN LTD

(22)Date of filing : 29.02.1996

(72)Inventor : KANEKO KEIICHI

(30)Priority

Priority number : 07246431 Priority date : 25.09.1995 Priority country : JP

(54) ORTHOGONAL FREQUENCY DIVISION MULTIPLE SIGNAL TRANSMISSION SYSTEM, TRANSMITTING DEVICE AND RECEIVING DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To prevent the occurrence of a code error by correcting the error of an amplitude character difference and a phase characteristic difference between an I-signal and a Q-signal.

SOLUTION: A transmission side transmits a known reference signal with a specified carrier among plural carriers constituting an OFDM signal, designates the carrier transmitting the known reference signal by a symbol number transmitted with the prescribed carrier, and sequentially changes and transmits them in a circle at every regular period. A reception side demodulates the reference signal in a decoding circuit 311 and a detection circuit 312 detects a transmission line characteristic. A first correction expression deviation holding circuit 313 calculates and stores a first correction expression from the detected transmission line characteristic. A first correction circuit 314 decodes the signals by using the correction expression. A second correction expression is newly calculated and corrected for the output signal of the correction circuit 314. Thus, a high speed change characteristic can be corrected.

